

Technical Data Sheet (TDS)

SAE 0W-20 API SN/CF

A very high quality mineral engine oil, which is suitable for most of 4-stroke gasoline and diesel cars and light trucks. By its selected composition, a very good resistance to oxidation and optimal detergent and dispersion properties are obtained. A strong oil film guarantees a high lubricating power.

APPLICATIONS

This oil can be applied in modern 4-stroke gasoline (multi valves, turbo, etc.) and 4-stroke diesel engines, with or without turbo.

FEATURES

Total engine protection: engine protection and cleanliness

PERFORMANCE

ACEA	A3/B4	PSA	B71 2295
API	SN/CF	VW	501 01
MB	229.1	VW	505 00

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.892
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	167
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	18.3
Viscosity index	ASTM D2270		122
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	10.1
Pour point	ASTM D6892	°C	-27
Sulfated Ash	ASTM D874	Mass %	1.03
Flash Point COC	ASTM D92	°C	222

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.