

Technical Data Sheet (TDS)

DENZ

SAE 5W-30 , CH-4/SJ

Semi Synthtetic

DENZ semi synthetic is heavy-duty diesel engine oil which helps to protect against the buildup of piston deposits for continuous engine efficiency. It exceeds performance limits in piston ring, cylinder liner and valve train wear tests for long engine life.

APPLICATION

These heavy duty engine oils are recommended for all types of diesel and gasoline engines where the manufacturer specifies the API service CH-4/SJ. They are especially suited for use in low temperature environments where extreme pumpability properties are required. These Oils are also suitable for on-road and off-road applications, including equipment that are exposed to extreme low temperature operations. This oil is suitable for use in moderate to high sulfur content fuel.

FEATURES & BENEFITS

- Improved oxidation stability to minimize deposit formation
- Higher TBN to extend protection from acids caused by combustion
- Better protection against valve train wear
- Improved low temperature performance
- Potential fuel economy improvement compared to conventional CH-4 heavy duty engine oils

PERFORMANCE STANDARDS

- API CH-4/SJ
- ACEA E7
- ACEA A3/B3/B4
- MB 228.3
- MAN 3275
- JASO Dh2

TYPICAL PROPERTIES

PARAMETERS	ASTM	UNIT	DENZ 5W-30
Kinematic Viscosity @ 104°F / 40°C	D7042	cSt	68.6
Kinematic Viscosity @ 212°F / 100°C	D7042	cSt	11.9
Viscosity Index (min)	D2270	-	171
Density @ 15°C / 60°F	D4052	g/cm ³	0.859
Flash Point (min)	D92	°C	234
Pour Point(max)	D97	°C	-45
TBN	D2896	mgKOH/g	11
CCS	D5293	m.Pa.S	<6600 (-30°C)

HEALTH & SAFETY, ENVIORMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil into drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS on our website: www.fubex.net

HEALTH & SAFETY:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, or exposed to hot sun or freezing conditions.

PROTECT THE ENVIRONMENT

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.