

Technical Data Sheet (TDS)

NEON

SAE 5W-30 , SJ-CF

Fully Synthetic

NEON is a superior quality fully synthetic engine oil formulated with high performance base stocks and premium additive technology which helps deliver outstanding engine protection and prevents the build-up of deposits and sludge in the engines operating in all driving conditions on highways and in the city.

APPLICATION

NEON is recommended for all naturally aspirated, fuel injected, turbocharged and multivalve passenger car engines without particulate filters.

FEATURES & BENEFITS

- Superior viscosity retention Oxidation resistant
- Outstanding wear and friction protection
- Excellent detergency and dispersancy
- Easy start at low temperatures
- Excellent protection against sludge and varnish build-up

PERFORMANCE STANDARDS

- API SJ-CF
- ACEA A3/B3
- ILSAC GF-2
-
-

TYPICAL PROPERTIES

PARAMETERS	ASTM	UNIT	NEON 5W-30
Kinematic Viscosity @ 104°F / 40°C	D7042	cSt	57.6
Kinematic Viscosity @ 212°F / 100°C	D7042	cSt	10.1
Viscosity Index (min)	D2270	-	165
Density @ 15°C / 60°F	D4052	g/cm ³	0.850
Flash Point (min)	D92	°C	224
Pour Point(max)	D97	°C	-42
TBN	D2896	mgKOH/g	6.0
CCS	D5293	m.Pa.S	<6600 (-30°C)

HEALTH & SAFETY, ENVIORMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil into drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS on our website: www.fubex.net

HEALTH & SAFETY:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, or exposed to hot sun or freezing conditions.

PROTECT THE ENVIRONMENT

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.