

Technical Data Sheet (TDS)

RULEX

SAE 15W-40 , SM-CF

Mineral

RULEX is premium quality mineral oil for gasoline and diesel engines, which can be used in all operating conditions (city traffic, road, motorways). It is particularly suited to turbo-charged engines and perfectly adapted to vehicles equipped with catalysts and using unleaded fuel.

APPLICATION

Recommended for gasoline fueled automobiles and light duty trucks requiring an API SM/CF.

FEATURES & BENEFITS

- Enables fast and easy start in extreme temperature conditions
- Particularly recommended for urban driving
- Oil film able to withstand high operating temperatures
- Protects engines against deposits Standard drain interval

PERFORMANCE STANDARDS

- API SM/CF
- ACEA A3/B3
- MB 229.1

TYPICAL PROPERTIES

PARAMETERS	ASTM	UNIT	RULEX 15W-40
Kinematic Viscosity @ 104°F / 40°C	D7042	cSt	110.3
Kinematic Viscosity @ 212°F / 100°C	D7042	cSt	15
Viscosity Index (min)	D2270	-	142
Density @ 15°C / 60°F	D4052	g/cm ³	0.880
Flash Point (min)	D92	°C	234
Pour Point(max)	D97	°C	-33
TBN	D2896	mgKOH/g	8
CCS	D5293	m.Pa.S	<7000 (-20°C)

HEALTH & SAFETY, ENVIORMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil into drains or the enviornment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS on our wevbsite: www.fubex.net

HEALTH & SAFETY:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. products should never be stored above 60°C , or exposed to hot sun or freezing conditions.

PROTECT THE ENVIRONMENT

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.