

## Technical Data Sheet (TDS)

### RULEX

SAE 20W-50 , SM-CF

Mineral

**RULEX** is premium quality mineral oil for gasoline and diesel engines, which can be used in all operating conditions (city traffic, road, motorways). It is particularly suited to turbo-charged engines and perfectly adapted to vehicles equipped with catalysts and using unleaded fuel.

### APPLICATION

Recommended for gasoline fueled automobiles and light duty trucks requiring an API SM/CF.

### FEATURES & BENEFITS

- Enables fast and easy start in extreme temperature conditions
- Particularly recommended for urban driving
- Oil film able to withstand high operating temperatures
- Protects engines against deposits Standard drain interval

### PERFORMANCE STANDARDS

- API SM/CF
- ACEA A3/B3
- MB 229.1

### TYPICAL PROPERTIES

PARAMETERS	ASTM	UNIT	RULEX 20W-50
Kinematic Viscosity @ 104°F / 40°C	D7042	cSt	117.8
Kinematic Viscosity @ 212°F / 100°C	D7042	cSt	20
Viscosity Index (min)	D2270	-	131
Density @ 15°C / 60°F	D4052	g/cm <sup>3</sup>	0.887
Flash Point (min)	D92	°C	236
Pour Point(max)	D97	°C	-30
TBN	D2896	mgKOH/g	8
CCS	D5293	m.Pa.S	<9500 (-15°C)

### HEALTH & SAFETY, ENVIORMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil into drains or the enviornment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS on our wevbsite: [www.fubex.net](http://www.fubex.net)

### HEALTH & SAFETY:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontantly to avoid the possible ingress of water and damage to drum markings. products should never be stored above 60°C , or exposed to hot sun or freezing conditions.

### PROTECT THE ENVIRONMENT

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.