

Technical Data Sheet (TDS)

ADVENT

SAE 10W-40 , SN

Semi Synthtetic

Advent is Semi synthetic, high-performance engine oil formulated specifically to meet the demanding needs of motorcycle engines. It is primarily for on-road, high-performance, 4-cycle sport bikes, however, it may be used in other types of on and off-road 4-cycle motorcycles. It is formulated to help offer outstanding protection in 4-cycle, V-Twin type engines, particularly those which are air cooled and tend to run hotter than other types of engines. Race 4T Nano XP provides excellent performance in common engine/transmission lubrication system or where the engine lubrication system is separate from the transmission system.

APPLICATION

Recommended for all 4-Stroke motorcycles including cruisers and off-road motorcycles.

FEATURES & BENEFITS

- Excellent shear stability
- Provides high temperature protection
- Outstanding wet clutch protection for maximum power transfer and smooth shifting
- Excellent wear and corrosion protection
- Maximizes power and acceleration
- Added protection against harmful deposits

PERFORMANCE STANDARDS

- API SN
- JASO MA2
-
-
-
-

TYPICAL PROPERTIES

PARAMETERS	ASTM	UNIT	ADVENT 10W-40
Kinematic Viscosity @ 104°F /40°C	D7042	cSt	95.2
Kinematic Viscosity @ 212°F /100°C	D7042	cSt	14.0
Viscosity Index (min)	D2270	-	152
Density @ 15°C /60°F	D4052	g/cm3	0.861
Flash Point (min)	D92	°C	232
Pour Point(max)	D97	°C	-38
TBN	D2896	mgKOH/g	7
CCS	D5293	m.Pa.S	<6800 (-25°C)

HEALTH & SAFETY, ENVIORMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil into drains or the enviornment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS on our wevbsite: www.fubex.net

HEALTH & SAFETY:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontal to avoid the possible ingress of water and damage to drum markings. products should never be stored above 60°C , or exposed to hot sun or freezing conditions.

PROTECT THE ENVIRONMENT

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.