

Technical Data Sheet (TDS)

ADVENT

SAE 20W-60 , SN

Mineral

Advent is an advanced Mineral Based engine oil designed to fulfill the rigorous requirements of motorcycle engines. It is specifically tailored for on-road, high-performance 4-cycle sport bikes but is also suitable for various other on and off-road 4-cycle motorcycles. Engineered to provide exceptional protection, it excels in 4-cycle, V-Twin engines, particularly those that are air-cooled and operate at higher temperatures compared to other engine types. Advent delivers outstanding performance in both integrated engine/ transmission lubrication systems and in systems where the engine and transmission lubrication are separate.

APPLICATION

Recommended for all 4-Stroke motorcycles including cruisers and off-road motorcycles.

FEATURES & BENEFITS

- Excellent shear stability
- Provides high temperature protection
- Outstanding wet clutch protection for maximum power transfer and smooth shifting
- Excellent wear and corrosion protection
- Maximizes power and acceleration
- Added protection against harmful deposits

PERFORMANCE STANDARDS

- API SN
- JASO MA2
-
-
-
-

TYPICAL PROPERTIES

PARAMETERS	ASTM	UNIT	ADVENT 20W-60
Kinematic Viscosity @ 104°F /40°C	D7042	cSt	212.2
Kinematic Viscosity @ 212°F /100°C	D7042	cSt	24.2
Viscosity Index (min)	D2270	-	145
Density @ 15°C /60°F	D4052	g/cm3	0.891
Flash Point (min)	D92	°C	238
Pour Point(max)	D97	°C	-28
TBN	D2896	mgKOH/g	7
CCS	D5293	m.Pa.S	<9500 (-15°C)

HEALTH & SAFETY, ENVIORMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil into drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS on our website: www.fubex.net

HEALTH & SAFETY:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, or exposed to hot sun or freezing conditions.

PROTECT THE ENVIRONMENT

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.