

Technical Data Sheet (TDS)

DEOX

SAE 50, CD/SF

Mineral

DEOX is designed to be used for passenger cars, light trucks as well as farm equipment, especially where single type of oil is preferred. This oil contains inhibitors to combat acids formation, oxidation and foaming. It is formulated with high quality mineral base stock and advance additive system.

APPLICATION

Gasoline and light duty diesel engines found in passenger cars. Farm and construction equipment, stationary diesel engines and fourstroke engines.

FEATURES & BENEFITS

- Superior viscosity retention
- Oxidation resistant
- Wear and friction protection
- Engine Cleanliness and low combustion residue
- Excellent detergency and dispersancy

PERFORMANCE STANDARDS

- API CD-SF
- CAT TO-2

TYPICAL PROPERTIES

PARAMETERS	ASTM	UNIT	DEOX SAE 50
Kinematic Viscosity @ 104°F / 40°C	D7042	cSt	214.10
Kinematic Viscosity @ 212°F / 100°C	D7042	cSt	20.1
Viscosity Index (min)	D2270	-	110
Density @ 15°C / 60°F	D4052	g/cm ³	0.896
Flash Point (min)	D92	°C	245
Pour Point(max)	D97	°C	-15
TBN	D2896	mgKOH/g	7
CCS	D5293	m.Pa.S	NA

HEALTH & SAFETY, ENVIORMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil into drains or the enviornment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS on our wevbsite: www.fubex.net

HEALTH & SAFETY:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. products should never be stored above 60°C , or exposed to hot sun or freezing conditions.

PROTECT THE ENVIRONMENT

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.