

Technical Data Sheet (TDS)

SPARK

SAE 20 , TC

Mineral

Spark is a lubricant which is designed to provide excellent performance in two-stroke engines like motorcycles, scooters and mopeds. Its composition is perfectly compatible with lead-free fuels. This is a high technology product combining a perfect balance of highly refined base stocks and the latest additives technology. It is specially formulated for use in oil injected as well as premixed gasoline/oil lubricated engines. Its increased performance provides protection against exhaust emissions and engine carbon deposits.

APPLICATION

SPARK oil is intended for use in two-stroke air cooled engines. Also suitable for motorcycles, scooters, mopeds, snow mobiles, lawn mowers, golf carts, chain saws and other two-stroke powered applications where API TC lubricants are recommended. oil is intended for use in two-stroke air cooled engines. Also suitable for motorcycles, scooters, mopeds, snow mobiles, lawn mowers, golf carts, chain saws and other two-stroke powered applications where API TC lubricants are recommended.

FEATURES & BENEFITS

- Excellent shear stability
- Provides high temperature protection
- Outstanding wet clutch protection for maximum power transfer and smooth shifting
- Excellent wear and corrosion protection
- Maximizes power and acceleration
- Added protection against harmful deposits

PERFORMANCE STANDARDS

- API TC
- JASO FD
- ISO EGD
-
-
-

TYPICAL PROPERTIES

PARAMETERS	ASTM	UNIT	SPARK SAE 20
Kinematic Viscosity @ 104°F /40°C	D7042	cSt	61
Kinematic Viscosity @ 212°F /100°C	D7042	cSt	9.2
Viscosity Index (min)	D2270	-	130
Density @ 15°C /60°F	D4052	g/cm3	0.880
Flash Point (min)	D92	°C	130
Pour Point(max)	D97	°C	-24
TBN	D2896	mgKOH/g	2

HEALTH & SAFETY, ENVIORMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil into drains or the enviornment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS on our wevbsite: www.fubex.net

HEALTH & SAFETY:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. products should never be stored above 60°C , or exposed to hot sun or freezing conditions.

PROTECT THE ENVIRONMENT

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.