

Technical Data Sheet (TDS)

SPRING

SAE 10W-40, SL

Semi Synthtetic

Spring is a high quality engine oil designed for four-stroke motorcycles. Spring is based on Semi Synthetic base oils and advanced additives to bring out the best in your machine. It is designed to ensure maximum power and performance, even under the most demanding riding conditions. Its anti-friction formulation is proven to increase acceleration compared to conventional motorcycle oils. Spring protects the engine, clutch, gears and allows the best functionality of these three critical parts of the motorcycle.

APPLICATION

Recommended for all 4-Stroke motorcycles including cruisers and off-road motorcycles.

FEATURES & BENEFITS

- Excellent shear stability
- Provides high temperature protection
- Outstanding wet clutch protection for maximum power transfer and smooth shifting
- Excellent wear and corrosion protection
- Maximizes power and acceleration
- Added protection against harmful deposits

PERFORMANCE STANDARDS

- API SL
- JASO MA2
-
-
-
-

TYPICAL PROPERTIES

| PARAMETERS | ASTM | UNIT | SPRING 10W-40 |
|-------------------------------------|-------|-------------------|---------------|
| Kinematic Viscosity @ 104°F / 40°C | D7042 | cSt | 95.6 |
| Kinematic Viscosity @ 212°F / 100°C | D7042 | cSt | 14.9 |
| Viscosity Index (min) | D2270 | - | 163 |
| Density @ 15°C / 60°F | D4052 | g/cm ³ | 0.869 |
| Flash Point (min) | D92 | °C | 229 |
| Pour Point(max) | D97 | °C | -38 |
| TBN | D2896 | mgKOH/g | 7 |
| CCS | D5293 | m.Pa.S | <6800 (-25°C) |

HEALTH & SAFETY, ENVIORMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil into drains or the enviornment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS on our wevbsite: www.fubex.net

HEALTH & SAFETY:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. products should never be stored above 60°C, or exposed to hot sun or freezing conditions.

PROTECT THE ENVIRONMENT

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.