

## Technical Data Sheet (TDS)

### SPRING

SAE 10W-60, SL

Semi Synthtetic

**Spring** is a high quality engine oil designed for four-stroke motorcycles. Spring is based on Semi Synthetic base oils and advanced additives to bring out the best in your machine. It is designed to ensure maximum power and performance, even under the most demanding riding conditions. Its anti-friction formulation is proven to increase acceleration compared to conventional motorcycle oils. Spring protects the engine, clutch, gears and allows the best functionality of these three critical parts of the motorcycle.

### APPLICATION

Recommended for all 4-Stroke motorcycles including cruisers and off-road motorcycles.

### FEATURES & BENEFITS

- Excellent shear stability
- Provides high temperature protection
- Outstanding wet clutch protection for maximum power transfer and smooth shifting
- Excellent wear and corrosion protection
- Maximizes power and acceleration
- Added protection against harmful deposits

### PERFORMANCE STANDARDS

- API SL
- JASO MA2
- 
- 
- 
- 

### TYPICAL PROPERTIES

PARAMETERS	ASTM	UNIT	SPRING 10W-60
Kinematic Viscosity @ 104°F /40°C	D7042	cSt	186
Kinematic Viscosity @ 212°F /100°C	D7042	cSt	25.9
Viscosity Index (min)	D2270	-	174
Density @ 15°C /60°F	D4052	g/cm3	0.861
Flash Point (min)	D92	°C	232
Pour Point(max)	D97	°C	-38
TBN	D2896	mgKOH/g	7
CCS	D5293	m.Pa.S	<6800 (-25°C)

### HEALTH & SAFETY, ENVIORMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil into drains or the enviornment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS on our wevbsite: [www.fubex.net](http://www.fubex.net)

### HEALTH & SAFETY:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. products should never be stored above 60°C , or exposed to hot sun or freezing conditions.

### PROTECT THE ENVIRONMENT

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.