

Technical Data Sheet (TDS)

NATURA LA

2T Stroke CNG/LNG - SAE 40 , SM

Mineral

NATURA LA is a premium performance, heavy-duty, & selected two-stroke low-ash crankcase oil specifically designed to lubricate a wide range of four-stroke natural gas and dual-fuel engines where low-ash oils are recommended. It is formulated with premium quality base oils and additive technology to provide exceptional oxidation and nitration resistance, extended oil and filter life, and outstanding wear protection.

APPLICATION

Gas-fueled (natural gas and LPG) spark ignition engines where conventional passenger car motor oils are recommended Naturally aspirated and turbo-charged gasoline engines in passenger cars where API SM or lower performance oils are specified Light truck gasoline engines where API SM or lower performance oils are specified Four-stroke gasoline engines in portable power equipment where the manufacturer recommends conventional passenger car motor oils of API SM or lower performance

FEATURES & BENEFITS

- Special detergent and ashless dispersant additive system preserve power and performance by providing good control of piston and ring deposits, even under high temperature conditions
- Good nitration resistance protects against CNG related valve deposits
- Very good thermal and oxidation stability
- Single oil for fleet owners with CNG, dual-fuel and gasoline vehicles

PERFORMANCE STANDARDS

- Caterpillar
- Wärtsilä
- MAN
- MTU
- GE - Jenbacher
- MWM (DEUTZ)
- Waukesha
- Perkins
- MDE
- MTU
- Superior STGV
- Jenbacher
- Commins
- Hyundai
- API CF (Diesel Fuel Application)

TYPICAL PROPERTIES

PARAMETERS	ASTM	UNIT	NATURA LA SAE 40
Kinematic Viscosity @ 104°F / 40°C	D7042	cSt	146.1
Kinematic Viscosity @ 212°F / 100°C	D7042	cSt	15.30
Viscosity Index (min)	D2270	-	106
Density @ 15°C / 60°F	D4052	g/cm ³	0.882
Flash Point (min)	D92	°C	256
Pour Point (max)	D97	°C	-18
TBN	D2896	Mg KOH/g	5.5
Sulphated ASH	D-871	WT %	0.5

HEALTH & SAFETY, ENVIORMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil into drains or the enviornment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS on our wevbsite: www.fubex.net

HEALTH & SAFETY:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontal to avoid the possible ingress of water and damage to drum markings. products should never be stored above 60°C , or exposed to hot sun or freezing conditions.

PROTECT THE ENVIRONMENT

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.