

Technical Data Sheet (TDS)

NATURA PRO

SAE 20W-50, SM

Mineral

NATURA PRO is a performance proven engine lubricant designed to provide faster and cleaner engine protection to make sure of longer engine life. It is designed for use in gas fuelled engines in passenger cars and light commercial vehicles. It has special additive system which resists wear under all operating conditions by forming a protective layer on contact surfaces. High viscosity index provides additional protection against wear at start-up and under high temperature operating conditions.

APPLICATION

Gas-fuelled (natural gas and LPG) spark ignition engines where conventional passenger car motor oils are recommended
 Naturally aspirated and turbocharged gasoline engines in passenger cars where API SM or lower performance oils are specified
 Light truck gasoline engines where API SM or lower performance oils are specified
 Four-stroke gasoline engines in portable power equipment where the manufacturer recommends conventional passenger car motor oils of API SM or lower performance

FEATURES & BENEFITS

- Specials detergent and ashless dispersant additive system preserves power and performance by providing good control of piston and ring deposits, even under high temperature conditions.
- Good nitration resistance protects against CNG related valve deposits
- Very good thermal and oxidation stability
- Single oil for fleet owners with CNG, dual-fuel and gasoline vehicles

PERFORMANCE STANDARDS

- API SM
- Suitable for use also where API SL, SJ or SG oils are specified

TYPICAL PROPERTIES

PARAMETERS	ASTM	UNIT	NATURA PRO 20W-50
Kinematic Viscosity @ 104°F / 40°C	D7042	cSt	171
Kinematic Viscosity @ 212°F / 100°C	D7042	cSt	19.1
Viscosity Index (min)	D2270	-	127
Density @ 15°C / 60°F	D4052	g/cm ³	0.869
Flash Point (min)	D92	°C	242
TBN	D2896	Mg KOH/gm	-29
CCS	D5293	°C	8900 (-15°C)

HEALTH & SAFETY, ENVIORMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil into drains or the enviornment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS on our wevbsite: www.fubex.net

HEALTH & SAFETY:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontal to avoid the possible ingress of water and damage to drum markings. products should never be stored above 60°C, or exposed to hot sun or freezing conditions.

PROTECT THE ENVIRONMENT

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.