

Technical Data Sheet (TDS)

VELORA ATF , TYPE A Mineral

VELORA ATF TYPE A is a multi-purpose transmission fluid, designed for use in automatic gearboxes, where Velora Type A Suffix A is quoted. Its special formula enables very smooth operation of torque converters and fluid couplings of automatic transmissions.

APPLICATION

VELORA ATF TYPE A is suitable for use in automatic transmissions of passenger cars and light duty trucks as well as in other power shift transmissions, industrial torque converters, power steering systems and manual transmissions, where a low-viscosity fluid of VELORA ATF TYPE A quality is specified.

FEATURES & BENEFITS

- Excellent oxidation stability
- High viscosity index
- Corrosion prevention
- Smoothens transmission process
- Foaming resistance
- Controlled friction properties

PERFORMANCE STANDARDS

- VELORA Type A Suffix A

TYPICAL PROPERTIES

PARAMETERS	ASTM	UNIT	VELORA DEXRON II
Kinematic Viscosity @ 104°F / 40°C	D7042	cSt	52.2
Kinematic Viscosity @ 212°F / 100°C	D7042	cSt	7.6
Viscosity Index (min)	D2270	-	106
Density @ 15°C / 60°F	D4052	g/ cm3	0.886
Flash Point (min)	D92	°C	220
Pour Point(max)	D97	°C	-27

HEALTH & SAFETY, ENVIORMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil into drains or the enviorment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS on our wevbsite:
www.fubex.net

HEALTH & SAFETY:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. products should never be stored above 60°C , or exposed to hot sun or freezing conditions.

PROTECT THE ENVIRONMENT

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.